


# The sky's the limit

EvolutionNext is our follow up to the Evolution Series. With award-winning reliability, advanced security, and versatile finishing options, our sustainable design will help your business thrive.



### **BASIC SPECIFICATIONS**

Configuration: BW MFP - Print/Copy/Scan/Optional Fax Speed: Letter: 50 ppm, Legal: 30 ppm, Ledger: 25 ppm (print only)

Warm Up Time: 14.4 seconds or less

First Page Out: Copy: 3.7 seconds Print: 4.3 seconds

Display: 10.1" Color Touch Screen Control Panel

 $\begin{tabular}{ll} \bf Memory/Hard\ Disk\ Drive:\ 4G\ RAM/\ 256GB\ SSD\ Standard, \\ 1TB\ HDD\ (option) \end{tabular}$ 

**Duplex:** Standard Stackless Duplex supports Statement  $(5.5" \times 8.5")$  to Ledger  $(12" \times 18")$ , 16 lb. Bond - 142 lb. Index (60 - 256 gsm)

Standard Output Tray: Statement  $-12'' \times 18''/500$ -sheets; up to 12"  $\times 48''$  Banner (single sheet)

Electrical Requirements: 120V, 60Hz, 12A;

220-240V, 50/60Hz, 7.2A

Typical Electricity Consumption (TEC): 120V: .63 kWh/week;

220V: .60 kWh/week

Dimensions: 23.7" W  $\times$  26.1" D  $\times$  31.1" H

Weight: 182 lbs

Maximum Monthly Duty Cycle: 300,000 Pages per Month

### PAPER SUPPLY

Paper Capacity: Standard 1,150-sheets; Maximum 7,150-sheets Standard Paper Sources: Dual 500-sheet Trays, 150-sheet MPT, Auto Selection/Switching

Standard Paper Size:

Tray 1 – 5.5" x 8.5" – 8.5" x 14" (statement to legal)
Tray 2 – 5.5" x 8.5" – 12" x 18", Custom Size
MPT: 5.5" x 8.5" – 12" x 18" (multiple); to 12" x 48" Banner (single)

## **Optional Paper Sources:**

**PF-7140** Dual 500-sheet Tray Option -  $5.5'' \times 8.5'' - 12'' \times 18''$  **PF-7150** Dual 1,500-sheet Tray Option -  $8.5'' \times 11''$  **PF-7120** 3,000-sheet Large Capacity Tray Option -  $8.5'' \times 11''$ 

# Paper Weight:

Trays/MPT: 14 lb. Bond — 166 lb. Index (52 — 300gsm)
Input Materials: Standard/Optional Trays: Plain, Bond,
Recycled, Preprinted, Vellum, Color, Pre-Punched, Thick, Thin,
High Quality, Letterhead, Envelope, Custom; MPT: Plain, Bond,
Recycled, Preprinted, Vellum, Color, Pre-Punched, Thick, Thin,
High Quality, Transparency (OHP), Coated, Index Tab, Label,
Letterhead, Envelope, Custom

# SECURITY SPECIFICATIONS

Guarded Access: LDAP, IP Filtering, Secure Print Release, SMTP Authentication, Create Encrypted PDF, Failed Authentication Lockout, Card Authentication.

Protected Data Storage: SSD/HDD Overwrite, AES 256 Data Storage Encryption, Trusted Platform Module, IEC-15408, Common Criteria (validation pending), IEEE 2600 Certified, HCD-PP Certified.

Secure Communication: TLS v1.3, SMB 3.1.1, HTTPS, ECDSA, FIPS 140-3 Encryption, S/ MIME, IPSec with HCD-PP, IPPS Printing (Over TLS), SCEP Certificated Enrollment, OCSP/CRL Certificates, 802.1X Ethernet Certificates, SHA 2 384.

Advanced Management: 3 Preset Security Level Configurations, Remote Management of Fleet, SNMP v3 Monitoring, SIEM/Syslog Monitoring, Secure Boot Check, Run Time Integrity Checks, Allow List.

# PRINT SPECIFICATION

Standard Controller: ARM Cortex-A53/1.6GHz
PDLs/Emulations: PCL6 (PCL XL/PCL 5c); PRESCRIBE, KPDL3
(PostScript3 compatible) AES Support, PDF, XPS/OpenXPS,
PPML, Microsoft WPP and Universal Print
Print Resolution: Up to 4800 x 1200 dpi

Fonts: 93 Fonts (PCL6), 136 Fonts (KPDL3), 4 Fonts (Calibri), 4 Fonts (Cambria), 1 Font Bitmap font, 79 Outline fonts OS Compatibility: Windows: 10/11; Server 2016/Server 2019/Server 2022/Server 2025; Mac OS X v10.0 or later; Chrome OS Mobile Printing: Apple AirPrint®, Mopria®, Kyocera Cloud Print and Scan (KCPS), KYOCERA Mobile Print, & KYOCERA MyPanel

Interfaces: Standard: 1000Base-T/100Base-Tx/10BASE-T (IPv6, IPv4, IPSec), IEEE 802.3az; Other Standard: USB 2.0 (Hi-Speed USB), USB 3.0 (Super-Speed USB)

Optional: IEEE 802.11a/b/g/n/ac (**IB-37** for 2.4/5GHz - **IB-38** for 2.4GHz), 10/100/1000BaseTX (**IB-53** for Dual NIC); IEEE 802.11b/g/n (**IB-51** for Wireless LAN Interface (supports up to 328.1 feet)

Network Print and Supported Protocols: HTTPS, FTPS, SNMP v1/v2c/v3, Raw Port (Port 9100) TCP/IP, IPv4, IPv6, DHCP LPR, DNS, WSD Scan/Print

**Drivers:** KX Driver, PCL Mini Driver, KPDL Mini Driver, Network Fax Driver, TWAIN Driver, WIA Driver, Status Monitor, Common Profile, Output to PDF, Security Watermark, Super Resolution, Color Optimizer, MAC Driver, Chrome Print Driver, Linux Driver, KX Driver with Distributed Printing, Windows Inbox Driver, SANE Driver

Utilities: KYOCERA Net Viewer, KYOCERA Net Device Manager, Quick Setup, KX PRESCRIBE Macro Generator, ID Register, Software Management Service, Upgrade Studio, Web Package Maker, Removal Tool, PDF Direct Print, Command Center RX;

PDF Direct Print, Command Center R. Kyocera Net Manager (option)

#### SCAN SPECIFICATION

Scan Type: Color and Black & White Scanner Scan Resolution: 600/400/300/200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF, JPEG, XPS, OpenXPS, PDF, Searchable PDF, MS Office File

Connectivity/Supported Protocols: 10 BASE-T/100 BASE-TX/1000 BASE-T (IPv6, IPv4, IPSec) TCP/IP, Hi-Speed USB 3.0

Scanning Functions: Scan-to-Folder (SMBv3), Scan-to-Email, Scan-to-FTPS over TLS, Scan-to-USB, PDF Digital Signatures, WSD Scan, DSM/SANE Scan, TWAIN Scan, Specified Color Removal, Border Erase, Preview

Original Size: Up to 11" x 17" (Glass)

Drivers: TWAIN/WIA/DSM-SANE Driver/WSD Scan

# OPTIONAL DOCUMENT PROCESSORS<sub>2</sub>

Acceptable Originals: 5.5" x 8.5" - 11" x 17"

**DP-7150:** Reverse Auto Document Processor/140-sheets Speed: Simplex: 80 ipm; Duplex: 48 ipm (BW/Color) Weight: Simplex: 13 lb. Bond — 90 lb. Index (35 — 160gsm) Duplex: 16 lb. — 32 lb. Bond (50 — 120gsm)

DP-7160: Dual Scan Document Processor/320-sheets Speed: Simplex: 137 ipm; Duplex: 274 ipm (BW/Color) Weights: Simplex: 13 lb. Bond – 120 lb. Index (35 – 220gsm) Duplex: 16 lb. – 120 lb. Index (50 – 220gsm)

# DP-7170 (with multi-feed and staple detection):

Dual Scan Document Processor/320-sheets Speed: Simplex: 137 ipm; Duplex: 274 ipm (BW/Color) Weights: Simplex: 13 lb. Bond — 120 lb. Index (35 — 220gsm) Duplex: 16 lb. — 120 lb. Index (50 — 220gsm)

# COPY SPECIFICATIONS

**Copy Resolution:** 600 x 600 dpi **Image Mode:** Text, Photo, Text/Photo, Graphic/Map

Continuous Copy: 1 — 9,999

Additional Features: Auto Magnification, Auto Paper Select, Combine Copy, Mirror Image, Rotate Copy, Border Erase, Split Copy, Margin Shift, Page Number, Form Overlay, Blank Page Skip, Specified Color Removal, Proof Copy, Preview, ID Card Copy Job Management: 1,000 User Codes, Job Build, Shortcut Keys, Repeat Copy

Magnification/Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 – 400% in 1% Step Increments Document Box: Custom/Job/USB Drive Box, Fax Box (w/option)

## OPTIONAL FAX SPECIFICATIONS

Fax Type: Fax System (option)

Type/Data Compression: G3 Fax/MMR, MR, MH, JBIG
Transmission Speed/Modem Speed: Less than

3 seconds/33.6 Kbps

Fax Memory: Standard 170 MB

Driver: Network Fax Driver

Fax Functions: Network Fax, Duplex Transmission and Reception, Encrypted Transmission and Reception, Polling Transmission and Reception, Broadcast, Fax Server Integration, Fax Dedicated Paper Feed Tray, Fax Forwarding to email or file arding to email or file

## SOLUTIONS AND SERVICES

## Remote Management

Kyocera Fleet Services ready! A highly secure cloud-based monitoring solution that offers real-time visibility into your fleet. Optimize device uptime and be notified when to replenish supplies. Streamline billing with seamless 3rd party application integration, allowing you to focus solely on your business.

## Printing Software

Cost Control & Security Cloud & Mobile Printer Management

## **Content Services**

Scan & Connect Intelligent Process Automation Enterprise Content Management

# IT Solutions

Technology Solutions Including solutions for Cloud and Data Centers Network Infrastructure Cybersecurity Solutions Collaboration Solutions

# **Consulting Services**

Including IT Health Check CIO as a Service Healthcare Compliance Backup and Recovery Planning

# Professional Services

Including Design and Architecture Project Implementation Project Management

# Managed Services

Including Help Desk Services Retainer Services and On-site Support

# **Cloud Ready Services:**

Kyocera Cloud Capture (KCC), Kyocera Cloud Information Manager (KCIM), Kyocera Cloud Print and Scan (KCPS)

# Output & Finishing Options<sub>3</sub>

## **OPTIONAL 250 SHEET INNER SHIFT TRAY JS-7110**

Stack Capacity: 250-sheets Paper Size: 8.5" x 11" - 11" x 17

Paper Weight: 14 lb. Bond - 166 lb. Index (52 - 300gsm)

## OPTIONAL 500 SHEET INTERNAL FINISHER DF-71004

Stack/Staple Capacity: 500-sheets/50-sheets

**Paper Size:**  $5.5'' \times 8.5'' - 12'' \times 18''$ 

Paper Weight: 14 lb. Bond - 166 lb. Index (52 - 300gsm)

Edge Staple Position: 3 Positions: Front: 1 Staple,

Edge: 1 Staple, Face: 2 Staples

Optional Punch: PH-7100 2/3 Hole Punch Unit,

supports 5.5" x 8.5" - 12" x 18"; 14 lb. Bond - 166 lb. Index

**Dimensions:** 19.4" W x 21" D x 6.9" H

### OPTIONAL 1.000 SHEET FINISHER DF-71204

Stack/Staple Capacity: Main Tray: 1,000-sheets/50-sheets (up to 24 lb. Bond [90gsm])

Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 14 lb. Bond — 166 lb. Index (52 — 300gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2/3 Hole Punch Unit, supports 5.5" x 8.5" - 12" x 18"; 14 lb. Bond - 166 lb. Index

**Dimensions:** 21.6" W x 24.4" D x 41.3" H

### OPTIONAL 4,000 SHEET FINISHER DF-71404

Stack/Staple Capacity: Main Tray (A): 4,000-sheets; Sub Tray (B): 200-sheets/65-sheets (24 lb. Bond [90gsm]) Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 14 lb. Bond - 166 lb. Index (52 - 300gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2/3 Hole Punch Unit, supports 5.5" x 8.5" - 12" x 18"; 14 lb. Bond -166 lb. Index Dimensions: 29" W x 26" D x 42" H

Optional Booklet Folder/Trifold Unit BF-730: (DF-7140)

Booklet Folder: supports 8.5" x 11", 8.5" x 14", 11" x 17" Fold Booklet (staple): 16 lb. - 24 lb. Bond (60 - 90gsm) 20-sheets; 25 lb. - 28 lb. Bond (91 - 105gsm) 13-sheets; Higher than 28 lb. Bond (Higher than 105 gsm) 1-sheet Fold Booklet (no staple): 16 lb. - 24 lb. Bond (60 - 90 gsm) 5-sheets; 25 lb. Bond - 72 lb. Index (91 - 120gsm) 3-sheets; 32 lb. Bond - 110 lb. Cover (121 - 256gsm) 1-sheet **Trifold:** supports 8.5" x 11" only: 16 lb. - 24 lb. Bond (60 - 90gsm) 5-sheets; 25 lb. Bond - 72 lb. Index (91 - 120gsm) 3-sheets

## Optional Multi-Bin Mailbox MT-730(B): (DF-7140)

7 Trays; supports: 16 lb. Bond - 90 lb. Index (60 - 163asm): Stack Capacity per bin: 100-sheets: 5.5" x 8.5", 8.5" x 11"; 50-sheets: 8.5" x 14". 11" x 17"

### OPTIONAL 4,000 SHEET FINISHER DF-71504

Stack/Staple Capacity: Main Tray (A): 4,000-sheets; Sub Tray (B): 200-sheets/100-sheets (up to 20lb. Bond [80qsm])

Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 14 lb. Bond - 166 lb. Index (52 - 300gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2/3 Hole Punch Unit, Supports 5.5" x 8.5" - 12" x 18"; 14 lb. Bond - 166 lb. Index Dimensions: 29" W x 26" D x 42" H

Optional Booklet Folder/Trifold Unit BF-9100: (DF-7150)

Booklet Folder: supports 8.5" x 11", 8.5" x 14", 11" x 17' Fold Booklet (staple): 14 lb. - 24 lb. Bond (52 - 90gsm) 20-sheets; 25 lb. - 28 lb. Bond (91 - 105gsm) 13-sheets; Higher than 28 lb. Bond (Higher than 105 gsm) 1-sheet Fold Booklet (no staple): 14 lb. - 24 lb. Bond (52 - 90gsm) 5-sheets; 24 lb. Bond - 28 lb. Index (91 - 105gsm) 3-sheets; 28 lb. Bond — 140 lb. Index (106 — 256gsm) 1-sheet **Trifold:** supports 8.5" x 11" only: 14 lb. — 24 lb. Bond (52 - 90gsm) 5-sheets; 25 lb. Bond - 28 lb. Index (91 — 105gsm) 3-sheets

#### ADDITIONAL OPTIONS

AK-7110 Bridge Unit Attachment Kit, JS-7100 Job Separator. HD-16 Large Capacity HDD (1TB), Banner Guide 10, Internet Fax Kit (A), Card Authentication Kit (B), Dual NIC (IB-53), Extended Range Wireless LAN NIC (IB-51), Thin Print option (UG-33), Printer Emulation option (UG-34), DT-730(B) Document Tray, Scan Extension Kit (A) for Text Searchable PDF; MS Office File, Keyboard Holder 10, Numeric Keypad (NK-7130), Cabinet Stand

- 1 Requires PF-7140
- 2 Only 1 Document Processor can be installed 4 Requires Bridge Unit Attachment Kit (AK-7110)
- 3 Only 1 Output Option can be installed

Specifications and design are subject to change without notice. For the latest on connectivity visit kyoceradocumentsolutions.us. TASKalfa, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Mopria is a trademark of Mopria Alliance, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.





225 Sand Road, PO Box 40008





**KYOCERA Document Solutions America** 

Fairfield, New Jersey 07004-0008, USA Tel: 973-808-8444



kyoceradocumentsolutions.us

**Kyocera Document Solutions Partner**